

BERKELEY HILLS FIRE COMPANY

..... STANDARD OPERATING GUIDELINES

CARBON MONOXIDE & NATURAL GAS WORKSHEET

LOCATION: DATE: TIME:

INVESTIGATION:

PPM AT ENTRY:

INITIAL HIGHEST PPM:

CONCENTRATION PER FLOOR:

GARAGE:

PPM:

DIVISION:

PPM:

DIVISION:

PPM:

DIVISION:

PPM:

DIVISION:

PPM:

FURNACE:

LOCATION:

MONITOR VENT PIPES: ☐

PPM:

LOOK FOR GAPS, SOOT, CORROSION: ☐

PPM:

MONITOR BURNERS: ☐

PPM:

PILOT LIGHT AND BLUE FLAME: ☐

PPM:

DUCT INSERT INTO CHIMNEY: ☐

PPM:

WATER HEATER:

LOCATION:

MONITOR VENT PIPES: ☐

PPM:

LOOK FOR GAPS, SOOT, CORROSION: ☐

PPM:

MONITOR BURNERS: ☐

PPM:

PILOT LIGHT AND BLUE FLAME: ☐

PPM:

DUCT INSERT INTO CHIMNEY: ☐

PPM:

FIREPLACE (GAS AND FUEL): LOCATION:

MONITOR AROUND FIREPLACE: ☐

PPM:

DAMPER OPEN?: ☐

VENTED PROPERLY?: ☐

FLU CLEAR?: ☐

INTAKE OPEN?: ☐

PILOT LIGHT AND BLUE FLAME: ☐

PPM:

STOVE:

LOCATION:

MONITOR OVEN AFTER WARMED UP: ☐

PPM:

MONITOR 24IN ABOVE BURNERS: ☐

PPM:

PILOT LIGHT AND BLUE FLAME: ☐

PPM:

PPM WITHIN ACCEPTED RANGE (5-8PPM): ☐

VENTED PPM: